



# NORDIC-POWER DC/UPS

<b>Document</b>		<b>MULTIGUARD</b>
<i>Product Identifier</i>	<i>Description</i>	
<b>Charging Unit w/Battery Protection and Alarm Unit</b>	<b>AC/DC SM Charger Preliminary Specifications</b>	<b>TYPE 904 120W</b>

Emission standards	EN50081-1	
Immunity standards	EN50082-1	
Harmonic emission	EN61000-3-2 , class A	
Indications	Green LED-power output. Red LED-power over-load	
Dimensions	Weight	330X376X108mm   4500gr.
Mounting method	Wall Mount Cabinet	
IP class	IP20	
Terminals	Input- output cables	
Battery connection	2X0.75sqmm RD/BK WIRE W/CONNECTORS	
Battery Protection	Relay min. voltage 20VDC	
Extra space for Battery	170X350X100mm(Std.2pcs.Brackets for 7.2AhBatt.)	

PS. DELIVERABLE AS: 13.6VDC and 27.2VDC



Article Number:	Preliminary		
Document Date:	12.06.01	Approved:	
Current Revision no.:		Page Number:	2
Current Revision Date:		Tot. pages:	2

- Batterieladegeräte
- LADix System
- DC/DC Wandler
- Netzgeräte AC/AC
- Netzgeräte AC/DC
- Steckernetzgeräte AC/AC
- Steckernetzgeräte AC/DC
- Wechselrichter DC/AC
- Notstromversorgung DC-UPS**